

RFT-805D



RFT-805D

TWIN AV to DVB-T

RFT-805D is designed for modulating two analogue stereo audio and video to COFDM multiplex.

It can be used for e.g. info channels and camera control systems.

Then info channel can be received with the standard DVB-T set-top box.

Assembly for **RFT-800** frame, 19" frame or stand-alone. Simple OSD programming with the remote control unit.

Rating: Not Rated Yet
3-5 Days

[Ask a question about this product](#)

Description

Features

- ? Info channel with DVB-T set-top box
- ? 2* analogue AV input, 1*DVB-T output
- ? CVBS, RGB, S-video and YPbPr inputs

Technical specification

- ? Video encoder MPEG-2, compliant to ISO/IEC13818-2
Max bit rate 14 Mbps
- ? Audio encoder MPEG audio layer 1/2 Compliant to ISO/IEC11172-3
Max bit rate 256 kbps

COFDM output

- ? FFT 2k mode

- ? Guard interval 1/32
- ? FEC 1/2, 2/3, 3/4, 5 /6, 7/8
- ? Output level 105 dBuV max
- ? Output frequency range 114 ... 858 MHz

General

- ? Operating voltage 16 VDC
- ? Power consumption 16VDC/0,8A
- ? Dimensions 72 mm*218 mm* 129 mm