

RFT-8X7



RFT-8X7

DVB-T/DVB-C/DVB-S/S2 -> IP STREAMER RFT-8X7 transforms digital DVB-T/C and DVB-S/S2 programs into IP transport stream. Then digital terrestrial and satellite TV programs can be received with PC, IP STB or Smart TV. RFT-8X7 is valid for both SD and HD programs. With one RFT-8X7 unit can be transmitted up to 50 programs (8 users). RFT-8X7 can be equipped with CI slot (option) for the most common CA modules. Assembly for RFT-800 system or stand-alone. Easy WEB control interface.

Rating: Not Rated Yet
3-5 Days
★★★★★

[Ask a question about this product](#)

Description

Features

- ? Digital TV programs with Smart TV
- ? SD and HD
- ? 50 programs as unicast or 8 programs as multicast

Technical specification

DVB-T/C demodulator

- ? Input frequency range 177,5 - 858 MHz
- ? Input level 45 ... 80 dBuV
- ? Automatic FEC decoder

8PSK/QPSK demodulator

- ? Input frequency range 950-2150 Mhz
- ? Max. 40 Msymb/s per transponder
- ? Input level -65 ... -25 dBm

? DVB-S/S2 compatible

IP output

? SPTS

? Max bit rate 40 Mbit/s

? Multicast and Unicast UDP streaming

? UpnP-DNLA 1.5 Server

? IGMP Server

? Support SAP (Service Announcement Protocol)

General

? Power supply 16VDC/1,1A

? Input connectors 3* F-female

? Output connector 1* RJ-45

? Dimensions 71 mm*214 mm* 149 mm